

JCT60 U.S. PTO  
04/04/00

Attorney Docket No. AIA-117

JCT60 U.S. PTO  
09/543011  
04/04/00

ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): Kiyoshi WASHINO and Akihiro TOCHI

For: FRAME KIT FOR IC CARD AND IC CARD USING THE SAME

Enclosed are:

- ☒ Specification and Claim(s).
- ☒ Oath or Declaration (executed).
- ☒ 10 sheet(s) of drawings (2 sets).
- ☒ An assignment of the invention to **J. S. T. Mfg. Co., Ltd.**
- ☐ Copy of \_\_\_\_\_ priority application(s).
- ☒ Return receipt of postcard.

The fee has been calculated as shown below:

CLAIMS AS FILED				
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE \$345/\$690
TOTAL CLAIMS	20-20		X \$9 \$18	\$
INDEP. CLAIMS	2-3		X \$39 \$78	\$
Fee for Multiple Dependent Claims \$130/\$260				
			TOTAL FILING FEE	\$690

- ☐ A Preliminary Amendment is attached.
- ☐ °Verified Statement claiming small entity status is enclosed.
- ☒ Charge \$~~690.00~~ to Deposit Account No. 18-0013 to cover the filing fee. A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge any fees under 37 C.F.R. 1.16 or 1.17 which may be required during the entire pendency of this application, or to credit any overpayment, to Deposit Account No. 18-0013. A duplicate copy of this sheet is enclosed.
- ☐ A check in the amount of \$\_\_\_ cover the filing fee is enclosed.
- ☒ Charge \$~~40.00~~ deposit Account No. 18-0013 to cover the recordal fee. A duplicate copy of this sheet is enclosed.
- ☒ Applicant's undersigned attorney/agent may be reached by telephone in our Washington D.C. Office at

(202) 955-3750.

All correspondence should be directed to our below listed address.

Date:

4/4/2000



Monica Millner  
Reg. No. 42,894

RADER, FISHMAN & GRAUER, P.L.L.C  
1233 20<sup>th</sup> Street, NW, Suite 501  
Washington, DC 20036  
Telephone: (202) 955-3750  
Facsimile: (202) 955-3751

## FRAME KIT FOR IC CARD AND IC CARD USING THE SAME

## BACKGROUND OF THE INVENTION

## Field of the Invention

5           The present invention relates to a frame kit for an IC card and an IC card using the same.

## Description of Related Art

          Portable information equipment represented by a notebook personal computer, an electronic notebook, and  
10 so forth generally comprises an IC card slot on which an IC card such as a PC card or a CF card is to be mounted. The feature of the portable information equipment can be expanded by mounting the IC card on the IC card slot. The IC card has a circuit board assembly constructed  
15 by mounting a connector for connection to the IC card slot on a circuit board, a frame holding the circuit board assembly, and a pair of metal panels covering upper and lower surfaces of the circuit board assembly. The whole thereof is formed in a card shape.

20           An IC card fabrication system is roughly classified into a mechanical fabrication system suitable for mass production and a manual fabrication system suitable for relatively multi-kind and small-quantity production. In the mechanical  
25 fabrication system, a metal panel is fixed to a frame

composed of a resin molded product, for example, using facilities such as ultrasonic welding. Contrary to this, in the manual fabrication system, a circuit board assembly and a frame are interposed between a pair of metal panels, and the metal panels are coupled by being pressed against each other with the human fingers and a jig, thereby assembling an IC card.

In a frame kit for an IC card (a frame and a pair of metal panels) for assembling by the manual fabrication system, engaging members which are locking-engaged with each other are respectively provided on sides of the pair of metal panels, for example. One of the engaging members has a claw, and the other engaging member has an engaging hole. In the case of the assembling, the engaging members are engaged with each other, and the claw is fitted in the engaging hole, so that the metal panels are coupled to each other and at the same time, the mounting of the metal panels on the frame is achieved (see JP-A-9-245143 (KOKAI), for example). The metal panels are provided so as to cover a side surface of the frame from outside, and the engaging members are locking-coupled to each other at the side surface of the frame.

In coupling the metal panels, however, the respective engaging members of the panels are

elastically deformed. Accordingly, it is not necessarily easy to align the claw and the engaging hole with each other, and it is difficult to perform an operation for coupling the panels.

5           Moreover, the length of the claw is very small. Even if the claw and the engaging hole are completely fitted to each other at a glance, the engagement may, in some cases, be actually incomplete. If such defective products are put on the market, the IC card  
10 may be disassembled in cases where it is given a large shock, for example, a case where it is dropped on the floor.

          The IC card generally has a key groove determined by a standard formed on its side end surface. For  
15 example, the CF card is provided with a long key groove leading from a front end to the vicinity of a rear end on its side surface. However, in such construction that the engaging members of the pair of metal panels cover the side surface of the frame, a key groove conforming  
20 to the standard cannot be provided on a side end surface of the frame. Consequently, it is difficult to realize a manual frame kit for a CF card.

#### SUMMARY OF THE INVENTION

          An object of the present invention is to provide  
25 a frame kit for an IC card which can be assembled easily

and reliably and an IC card using the same.

Another object of the present invention is to provide a frame kit for an IC card capable of providing a good erroneous insertion preventing key on a side surface of a frame, and an IC card using the same.

A frame kit for an IC card in the present invention comprises a frame for defining an internal space of an IC card; a first panel integrated with the frame by simultaneous molding, for example, and having a first locking member which projects toward the internal space from an inner wall of the frame; and a second panel having a second locking member which is engaged with the first locking member of the first panel inside the frame.

In the construction of the present invention, the first panel is integrated with the frame by simultaneous molding, for example. Accordingly, the amount of projection of the first locking member of the first panel from the inner wall of the frame can be defined with high precision. Further, the amount of elastic deformation of the first panel at the time of the engagement between the first and second locking members is very small. Consequently, the first locking member is hardly displaced. Accordingly, it is easy to align the first and second locking members with each other

at the time of the engagement, and it is possible to engage the first locking member and the second locking member easily and reliably.

It is preferable that one of the first locking member and the second locking member has a locking claw, and the other locking member has an engaging hole with which the locking claw is engaged. It is more preferable that the second locking member is composed of an elastic member. In this case, the locking claw is introduced into the engaging hole mainly by the elastic deformation of the second locking member, so that the first and second locking members are snap-coupled to each other. Since the first locking member is hardly deformed at the time of the snap coupling, the locking claw can be fitted in the engaging hole easily and reliably. The locking claw which has been completely fitted in the engaging hole once does not easily slip off the engaging hole. Accordingly, the IC card may not be disassembled after being assembled.

In the construction of the present invention, when the first and second panels are pressed against each other, the first locking member and the second locking member are engaged with each other inside the frame. Therefore, the first and second panels need not be provided so as to surround the outside of the frame.

Accordingly, an outer side surface of the frame can be exposed. If the present invention is applied to an IC card such as a CF card which must be provided with a key groove for preventing erroneous insertion from a front end to the vicinity of a rear end of its side surface, therefore, a good key groove can be provided in the frame. Consequently, it is possible to provide a good manual frame kit for a CF card.

In such construction that a metal panel covers an outer surface of a frame, an end surface of the panel is exposed. Accordingly, the appearance of an IC card is not necessarily desirable. Moreover, the end surface of the panel must be prevented from forming a sharp edge by being subjected to finish processing. In the construction of the present invention in which the paired panels are engaged with each other inside the frame, edges of the panels can be contained in the frame or in an internal space of the frame. Accordingly, the appearance of the IC card is improved, and end surfaces of the panels need not be subjected to finish processing.

Furthermore, one of the panels and the frame are integrated with each other by the simultaneous molding, for example. Accordingly, the amount of deformation of the frame is significantly smaller, as compared with



that in a case where the panels and the frame are individual components to be assembled. Therefore, the IC card has good durability against an external force. Further, the first panel and the frame can be handled  
5 as one component, so that the number of components can be reduced. This also makes it easier to assemble the IC card.

It is preferable that the first locking member is implanted in the frame, and is held in the frame with  
10 its front end projected toward the internal space from the inner wall of the frame.

In this construction, the first locking member is hardly deformed because it is implanted in the frame. Therefore, it is easier to align and engage the first  
15 locking member and the second locking member with each other.

It is preferable that the frame has an outer surface exposed toward the outside of the IC card to form a side surface in the direction in which the IC  
20 card is inserted. It is preferable that an erroneous insertion preventing key for preventing the IC card from being inserted in a wrong posture into an IC card slot is formed on the outer surface of the frame, and the first panel is integrated with the frame in a state where  
25 an area where the erroneous insertion preventing key

is formed is ensured, that is, a state where the area is avoided.

In this construction, the outer surface of the frame is exposed as a side surface of the IC card after the IC card is assembled, and the erroneous insertion preventing key is provided on the outer surface of the frame.

In the present invention, it is possible for the panel not to cover the outer surface of the frame.

Therefore, the present invention is applied to an IC card (for example, a CF card) conforming to a standard which requires the erroneous insertion preventing key to be provided extending from a front end to the vicinity of a rear end on a side surface of the card, therefore, it is possible to provide a manual frame kit conforming to such a standard.

It is preferable that the second panel has a positioning member (for example, an elastic positioning member) which is abutted against the inner wall of the frame for positioning the second panel elastically, for example, with respect to the frame.

In this construction, the second panel is positioned with respect to the frame by abutting the positioning member against the inner wall of the frame elastically, for example. That is, the elastic

positioning member is abutted against the frame, for example, to press the frame outward. The second panel is pressed toward the center of the frame by its reaction. Accordingly, it is possible to reliably  
5 arrange the second panel in a regular position, and it is possible to reliably prevent displacement after the assembling.

It is preferable that the elastic positioning member is provided integrally with the second panel.  
10 It is more preferable that the elastic positioning members are provided on both sides of the second panel. Further, the positioning elastic member may be projected toward the inner wall of the frame from the second locking member.

15 An IC card according to the present invention comprises the frame kit having the above-mentioned features and a circuit board assembly constructed by mounting the connector on the circuit board, and is constructed by containing the circuit board assembly  
20 between the first panel and the second panel.

In this construction, the panels can be easily coupled to each other by the engagement between the first and second locking members. Moreover, the panels can be reliably coupled to the frame. Therefore, the  
25 IC card may not be disassembled.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an exploded perspective view of a CF card according to an embodiment of the present invention;

10 Fig. 2 is a bottom view of a frame panel assembly;

Fig. 3 is a diagram showing the shape of a side surface of the frame panel assembly;

Fig. 4 is a cross-sectional view taken along a line A - A shown in Fig. 2;

15 Figs. 5A and 5B are diagrams for explaining the construction of a second panel:

Fig. 6 is a cross-sectional view of a CF card for explaining assembling;

20 Figs. 7A to 7C are cross-sectional views of a principal part for graphically showing how a first locking member and a second locking member are engaged with each other;

Figs. 8A and 8B are diagrams for explaining a second panel according to another embodiment of the present invention;

25

Fig. 9 is a cross-sectional view of a principal part of a CF card according to the embodiment shown in Figs. 8A and 8B; and

Figs. 10A to 10C are cross-sectional views of a principal part for graphically showing how a second locking member and a first locking member are engaged with each other in the embodiment shown in Figs. 8A and 8B.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 In an embodiment described below, description is made of a case where the present invention is applied to a CF card. However, the present invention is also applicable to an IC card conforming to another standard, for example, a PC card or a small PC card.

15 Fig. 1 an exploded perspective view showing the construction of a CF card 1 according to an embodiment of the present invention. Referring to Fig. 1, the CF card 1 comprises a circuit board assembly 5, a frame 4 for defining an internal space of the CF card 1 and  
20 holding the circuit board assembly 5, a first panel 6 for covering an upper surface of the circuit board assembly 5, and a second panel 7 for covering a lower surface of the circuit board assembly 5. The circuit board assembly 5 has a printed circuit board 2 and a  
25 connector 3 attached to a front end of the printed

circuit board 2. The first panel 6 is positioned above the printed circuit board 2 in a state where the CF card 1 is normally used. The frame 4 and the first panel 6 are integrated with each other by simultaneous molding, thereby constituting a frame panel assembly 8.

The connector 3 is used for the electrical connection between a CF card slot (not shown) and the printed circuit board 2, and comprises a pair of first projections 9 in its side parts. Description is now made by taking the side of the connector 3 connected to the CF card slot as the front.

The connector 3 has a plurality of contacts (not shown) projecting backward. The contacts are soldered to the bottom surface of the printed circuit board 2. The mounting of the connector 3 on the printed circuit board 2 is achieved by the soldering.

Fig. 2 is a bottom view of the frame panel assembly 8. The frame panel assembly 8 is obtained by integrating the first panel 6 composed of a conductive plate in an approximately rectangular shape with the frame 4 by simultaneous molding. For example, it is formed by injection molding the frame 4 on the first panel 6.

The frame 4 has an approximately U shape, and defines an internal space of the CF card in its inner

part. The frame 4 comprises a pair of opposite side beams 11 and a rear end beam 12 for connecting respective rear ends of the side beams 11.

5 An engaging projection 13 projecting inward is formed at a front end of each of the side beams 11. The paired engaging projections 13 are respectively engaged with the first projections 9 of the connector 3 to hold the connector 3 in containing the circuit board assembly 5 in the frame panel assembly 8.

10 A second projection 14 projecting inward is provided in a position near the front of each of the side beams 11 a little beyond the center thereof. Further, a third projection 15 is provided in a position near the rear of each of the side beams 11 a little beyond  
15 the center thereof. A fourth projection 16 is provided at a rear end of each of the side beams 11. Engaging portions 14a, 15a, and 16a for holding the printed circuit board 2 are respectively formed on upper surfaces of the second, third, and fourth projections  
20 14, 15, and 16. A conductive portion 17 is provided in the vicinity of the rear end of each of the side beams 11. The conductive portion 17 is obtained by winding a metal member extending downward from the first panel 6 around the side beam 11.

25 Fig. 3 is a diagram showing the shape of a side

surface of the frame panel assembly 8. An outer side surface 11a of the side beam 11 is exposed outward, to form a side surface of the CF card 1. An erroneous insertion preventing key 18 for preventing the CF card 1 from being inserted in a wrong posture into the CF card slot is formed on the outer side surface 11a. The erroneous insertion preventing key 18 extends from a front end of the side beam 11 in the frame 4 to a position near the rear of the side beam 11 a little beyond the center thereof. The width of the erroneous insertion preventing key 18 differs between the right and left outer side surfaces 11a. Consequently, the CF card 1 is prevented from being inserted into the CF card slot (not shown) in a wrong posture, for example, such a posture that it is turned upside down. Further, the erroneous insertion preventing key 18 is closed at the rear of the CF card 1. Accordingly, the CF card 1 cannot be also inserted into the CF card slot with it being laterally inverted.

Referring to Fig. 2 again, the rear end beam 12 has a pair of grooves 20 and 21 extending along the length of the rear end beam 12 on its inner wall 12a. The grooves 20 and 21 respectively have pairs of positioning abutting portions 20a and 21a at both their ends.



First locking members 22 are provided in two portions spaced apart from each other in each of the side beams 11 in the frame 4.

Fig. 4 is a cross-sectional view taken along a line A - A shown in Fig. 2. Fig. 4 illustrates the CF card 1 in the direction in which it is normally used.

The first locking member 22 comprises a hanging portion 23 hanging toward the inside of the CF card 1 from a side edge of the first panel 6 and entering the side beam 11 and a locking claw 24 folded inward from a front edge 23a of the hanging portion 23. The first locking member 22 is thus implanted in the side beam 11 in the frame 4. A front end 24a of the locking claw 24 projects toward an internal space of the CF card 1 almost perpendicularly from an inner wall 11b of the side beam 11. Since the first panel 6 and the frame 4 are integrated with each other by simultaneous molding, the amount of projection of the locking claw 24 from the inner wall 11b is defined with high precision.

When the frame panel assembly 8 and the second panel 7 are coupled to each other, the first locking member 22 is engaged with a second locking member 34 provided in the second panel 7 inside the frame 4, so that both the panels 6 and 7 are coupled to each other.

As indicated by a two-dot and dash line in Fig. 4, the second locking member 34 comprises a raised portion 41 bent upward (toward the inside of the CF card) and molded along the inner wall 11b of the side beam 11 in the frame 4 from a side 7a of the second panel 7, a guiding portion 42 extending obliquely toward the inside of the frame 4 from a front end 41a of the raised portion 41 for guiding the locking claw 24, and an engaging hole 43 formed in the raised portion 41, to constitute an elastic member as a whole.

Fig. 5A is a plan view showing the construction of the second panel 7, and Fig. 5B is a side view of the second panel 7 as viewed from a direction indicated by an arrow R in Fig. 5A.

The second panel 7 is a plate-shaped member in an approximately rectangular shape composed of a conductive plate. The second panel 7 has a folded member 31 folded upward (toward the inside of the CF card 1) from both the sides 7a over nearly the full lengths of the sides 7a.

The second panel 7 comprises a pair of rotating and engaging members 32 and 33 on its rear end side 7b. The paired rotating and engaging members 32 and 33 respectively have predetermined widths along the rear end side 7b, and are in shapes respectively aligned with

a pair of grooves 20 and 21 formed in the frame 4.

Second locking members 34 are respectively formed in two portions spaced apart from each other on each of the sides 7a. Further, a conductive member 35  
5 extending upward is provided in the vicinity of the rear end of each of the sides 7a.

The procedure for assembling the CF card 1 will be described.

Referring to Fig. 6, the printed circuit board  
10 2 is fitted in the engaging portions 14a, 15a, and 16a of the second, third, and fourth projections 14, 15, and 16 in a state where the frame panel assembly 8 is turned over, so that the circuit board assembly 5 is held in the frame 4.

15 Thereafter, the paired rotating and engaging members 32 and 33 in the second panel 7 are respectively engaged with the grooves 20 and 21 formed in the rear end beam 12 in the frame 4 with the frame panel assembly 8 held with one of worker's hands and with the second  
20 panel 7 obliquely applied to the frame panel assembly 8 with the other hand.

The worker presses the second panel 7 against the frame 4 in such a manner that the first and second panels 6 and 7 are pressed against each other with the fingers  
25 of both the hands. Consequently, the first locking

member 22 and the second locking member 34 are snap-coupled to each other, so that the first and second panels 7 and 8 are locking-coupled to each other.

At this time, the first locking member 22 and the second locking member 34 are coupled to each other inside the frame 4, so that the outer side surface 11a of the side beam 11 is exposed. Accordingly, the erroneous insertion preventing key 18 is not covered with the panels 6 and 7.

In a state where the first and second panels 6 and 7 and the frame 4 are coupled to each other, the conductive member 35 formed in the second panel 7 is abutted against the conductive portion 17 in the opposite first panel 6, thereby obtaining stable electrical conduction between both the panels 6 and 7.

Figs. 7A to 7C are cross-sectional views of a principal part for graphically showing how the first locking member 22 and the second locking member 34 are engaged with each other. If the first panel 6 and the second panel 7 are pressed against each other from the state shown in Fig. 7A, the guiding portion 42 guides the corresponding locking claw 24 to the engaging hole 43, as shown in Fig. 7B. At this time, an area in the vicinity of the raised portion 41 and the guiding portion 42 in the second panel 7 are elastically

deformed toward the inside of the frame 4. On the other hand, the first locking member 22 which is implanted in the side beam 11 is hardly deformed. Therefore, the first and second locking members 22 and 34 can be aligned with each other with high precision. Thereafter, when the locking claw 24 extending inward is contained in the engaging hole 43, as shown in Fig. 7C, the raised portion 41 and the guiding portion 42 in the first panel 6 which are elastically deformed inward are respectively restored into their original shapes. The first and second locking members 22 and 34 are aligned with each with high precision, and the first locking member 22 is hardly deformed. Accordingly, both the first and second locking members 22 and 34 can be engaged with each other easily and reliably.

The raised portion 41 and the guiding portion 42 are thus elastically deformed, and the locking claw 24 and the engaging hole 43 are snap-engaged with each other when the elastic deformation is restored. Accordingly, both the raised portion 41 and the guiding portion 42 are deeply engaged with each other, to enter a locked state. If the first and second locking members 22 and 34 are engaged with each other once, therefore, the CF card 1 is not disassembled.

When the second panel 7 is pressed against the

frame panel assembly 8, a sound in the snap coupling between the locking members 22 and 34 is emitted, thereby creating a good feeling at the time of coupling both the panels 6 and 7.

5           The folded member 31 is provided over nearly the whole areas of both the sides 7a of the second panel 7. After the CF card 1 is assembled, therefore, the end surface of the second panel 7 is not exposed, thereby producing a good appearance.

10           As described in the foregoing, according to the present embodiment, the first panel 6 is integrated with the frame 4 by simultaneous molding. Accordingly, the amount of projection of the first locking member 22 in the first panel 6 from the inner wall 11b of the frame  
15           4 can be defined with high precision. Further, the amount of elastic deformation of the first panel 6 at the time of the engagement between the first and second locking members 22 and 34 is very small. Consequently, the first locking member 22 is hardly displaced.

20           Accordingly, it is easy to align the first and second locking members 22 and 34 with each other at the time of the engagement. Further, it is possible to engage the first locking member 22 and the second locking member 34 with each other easily and reliably.

25           When the first and second panels 6 and 7 are

pressed against each other, the first locking member 22 and the second locking member 34 are engaged with each other inside the frame 4. Accordingly, the outer side surface 11a of the frame 4 can be exposed.

5 Consequently, a good erroneous insertion preventing key 18 can be provided in the frame 4.

Furthermore, the first panel 6 and the frame 4 are integrated with each other. Accordingly, the amount of deformation of the frame 4 is significantly smaller,  
10 as compared with that in a case where the panel 6 and the frame 4 are individual components to be assembled. Therefore, the CF card 1 can have good durability against an external force. Further, the first panel 6 and the frame 4 can be substantially handled as one  
15 component, so that the number of components can be reduced. Consequently, the CF card 1 can be assembled more easily.

Figs. 8A and 8B are diagrams for explaining the construction of a second panel 107 in another embodiment  
20 in a CF card according to the present invention. The second panel 107 is used in place of the second panel 7 in the embodiment shown in Fig. 1. The second panel 107 in the present embodiment differs from the second panel 7 shown in Figs. 5A and 5B in that there are  
25 provided elastic positioning members 50 for positioning

the second panel 107 with respect to a frame 4.

In the embodiment shown in Figs. 8A and 8B, a second locking member 34A is formed extending from a front end of each of sides 107a of the second panel 107 to a position near a rear end of the side 107a a little beyond the center thereof.

The second locking member 34A comprises two engaging holes 53. The engaging holes 53 are respectively fitted in locking claws 24 of a first locking member 22 which are provided at corresponding positions, to couple both panels 6 and 107.

When the second panel 107 and the first panel 6 are coupled to each other in the present embodiment, the second locking member 34A is engaged with the first locking member 22. Referring to Fig. 9, the second locking member 34A comprises a raised portion 51 bent upward (toward the inside of the CF card 1) and formed along an inner wall 11b of a side beam 11 in a frame 4 from the side 107a of the second panel 107, a guiding portion 52 extending obliquely toward the inside of the frame 4 from a front end 51a of the raised portion 51 for guiding the locking claw 24, two engaging holes 53 formed in the raised portion 51, and upward elastic positioning members 50 formed by raising upper parts of the engaging holes 53 outward (toward the inner wall



11b of the frame 4) from the front end 51a of the raised portion 51, constitute an elastic member as a whole.

Figs. 10A to 10C are cross-sectional views of a principal part for graphically showing how the first locking member 22 and the second locking member 34A are engaged with each other.

As shown in Fig. 10A, the first panel 6 and the second panel 107 are pressed against each other.

When the panels 6 and 7 are locked to each other, the guiding portion 52 guides the corresponding locking claw 24 to the engaging hole 53, as shown in Fig. 10B. At this time, an area in the vicinity of the raised portion 51 and the guiding portion 52 in the second panel 6 are elastically deformed toward the inside of the frame 4. Thereafter, when the locking claw 24 extending inward is contained in the engaging hole 53, as shown in Fig. 10C, the raised portion 51 and the guiding portion 52 in the first panel 6 which are elastically deformed inward are restored to their original shapes. At this time, the elastic positioning members 50 are abutted against the frame 4, to press the frame 4 outward.

The elastic positioning members 50 are elastically abutted against the inner wall 11b of the frame 4, so that the second panel 107 is positioned with

respect to the frame 4. That is, the elastic positioning members 50 are abutted against the frame 4, to press the frame 4 outward. The second panel 107 is pressed toward the center of the frame 4 by its reaction.

- 5 Accordingly, it is possible to reliably arrange the second panel 107 at a regular position, and it is possible to reliably prevent displacement after the assembling.

Although the present invention has been described  
10 and illustrated in detail, it is clearly understood that the same is by way of illustration and example only and is not to be taken by way of limitation, the spirit and scope of the present invention being limited only by the terms of the appended claims.

- 15 The present invention claims the conventional priority benefits of Japanese Patent Application No. 11-100415 filed with the Japanese Patent Office on April 7, 1999, the disclosure of which is incorporated hereinto by reference.

What is claimed is:

1. A frame kit for an IC card, comprising:  
a frame for defining an internal space of an IC card;  
5 a first panel integrated with the frame and having a first locking member which projects toward the internal space from an inner wall of the frame; and  
a second panel having a second locking member which is engageable with the first locking member of  
10 the first panel inside the frame.  
2. The frame kit according to claim 1, wherein the first panel is integrated with the frame by simultaneous molding.  
3. The frame kit according to claim 1, wherein  
15 one of the first locking member and the second locking member has a locking claw, and the other locking member has an engaging hole with which the locking claw is engaged.  
4. The frame kit according to claim 1, wherein  
20 the second locking member is composed of an elastic member.  
5. The frame kit according to claim 1, wherein edges of the first panel and the second panel are contained in the frame or in an internal space of the  
25 frame.

6. The frame kit according to claim 1, wherein the first locking member is implanted in the frame, and is held in the frame with its front end projected toward the internal space from the inner wall of the frame.

7. The frame kit according to claim 1, wherein the frame has an outer surface exposed toward an outside of the IC card to form a side surface in a direction in which the IC card is inserted.

8. The frame kit according to claim 7, wherein an erroneous insertion preventing key for preventing the IC card from being inserted in a wrong posture into an IC card slot is formed on the outer surface of the frame, and

the first panel is integrated with the frame in a state where an area where the erroneous insertion preventing key is formed is ensured.

9. The frame kit according to claim 1, wherein the second panel has a positioning member which is abutted against the inner wall of the frame for positioning the second panel with respect to the frame.

10. The frame kit according to claim 9, wherein the positioning member is an elastic positioning member which is elastically abutted against the inner wall of the frame.

11. An IC card comprising:

a frame for defining an internal space of an IC card;

a first panel integrated with the frame and having

5 a first locking member which projects toward the internal space from an inner wall of the frame;

a second panel having a second locking member which is engageable with the first locking member of the first panel inside the frame; and

10 a circuit board assembly constructed by mounting the connector on the circuit board,

the circuit board assembly being contained between the first panel and the second panel.

12. The IC card according to claim 11, wherein

15 the first panel is integrated with the frame by simultaneous molding.

13. The IC card according to claim 11, wherein

one of the first locking member and the second locking member has a locking claw, and the other locking member has an engaging hole with which the locking claw is engaged.

14. The IC card according to claim 11, wherein

the second locking member is composed of an elastic member.

25 15. The IC card according to claim 11, wherein

edges of the first panel and the second panel are contained in the frame or in an internal space of the frame.

16. The IC card according to claim 11, wherein  
5 the first locking member is implanted in the frame, and is held in the frame with its front end projected toward the internal space from the inner wall of the frame.

17. The IC card according to claim 11, wherein  
10 the frame has an outer surface exposed toward an outside of the IC card to form a side surface in a direction in which the IC card is inserted.

18. The IC card according to claim 17, wherein  
an erroneous insertion preventing key for  
15 preventing the IC card from being inserted in a wrong posture into an IC card slot is formed on the outer surface of the frame, and

the first panel is integrated with the frame in a state where an area where the erroneous insertion  
20 preventing key is formed is ensured.

19. The IC card according to claim 11, wherein  
the second panel has a positioning member which is abutted against the inner wall of the frame for positioning the second panel with respect to the frame.

25 20. The IC card according to claim 19, wherein

the positioning member is an elastic positioning member which is elastically abutted against the inner wall of the frame.

(1) (2)  
(3) (4)  
(5) (6)  
(7) (8)  
(9) (10)  
(11) (12)  
(13) (14)  
(15) (16)  
(17) (18)  
(19) (20)  
(21) (22)  
(23) (24)  
(25) (26)  
(27) (28)  
(29) (30)  
(31) (32)  
(33) (34)  
(35) (36)  
(37) (38)  
(39) (40)  
(41) (42)  
(43) (44)  
(45) (46)  
(47) (48)  
(49) (50)  
(51) (52)  
(53) (54)  
(55) (56)  
(57) (58)  
(59) (60)  
(61) (62)  
(63) (64)  
(65) (66)  
(67) (68)  
(69) (70)  
(71) (72)  
(73) (74)  
(75) (76)  
(77) (78)  
(79) (80)  
(81) (82)  
(83) (84)  
(85) (86)  
(87) (88)  
(89) (90)  
(91) (92)  
(93) (94)  
(95) (96)  
(97) (98)  
(99) (100)

## ABSTRACT OF THE DISCLOSURE

A frame kit for an IC card including a frame for defining an internal space of an IC card, a first panel integrated with the frame and having a first locking member which projects toward the internal space from an inner wall of the frame, and a second panel having a second locking member which is engageable with the first locking member of the first panel inside the frame. The first panel is integrated with the frame by simultaneous molding, for example. The second locking member is preferably composed of an elastic member.



FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A





FIG. 5B






FIG. 7A




FIG. 7B




FIG. 7C





FIG. 8A



F I G. 8 B






FIG. 9




FIG. 10A




FIG. 10B





FIG. 10C



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Declaration and Power of Attorney For Patent Application

## 特許出願宣言書及び委任状

## Japanese Language Declaration

## 日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。 As a below named Inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載されたと通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者である（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

FRAME KIT FOR IC CARD AND IC CARD USING  
THE SAME

上記発明の明細書（下記の欄でx印がついていない場合は、the specification of which is attached hereto unless the following box is checked: 本書に添付）は、

☐ 月 日に提出され、米国出願番号または特許協定条約  
国際出願番号を \_\_\_\_\_ とし、  
(該当する場合) \_\_\_\_\_ に訂正されました。☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT International Application Number  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

0698-1

PTO/SB/10619-95

Approved for use through 8/30/98 OMB 0551-0032

(Slight Modification was made at priority claiming portion.)

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Japanese Language Declaration

## (日本語宣言書)

私は、米国法典第35編119条(a)(4)項又は365条(b)項に基き下記の、米国以外の国の少なくとも一か国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願について外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

## Prior Foreign Application(s)

## 外国での先行出願

## Priority Claimed

## 優先権主張

11-100415

Japan

April 7, 1999

(Number)

(Country)

(Day/Month/Year Filed)

(番号)

(国名)

(出願年月日)

☒☐

Yes

No

はい

いいえ

(Number)

(Country)

(Day/Month/Year Filed)

(番号)

(国名)

(出願年月日)

☐☐

Yes

No

はい

いいえ

私は、第35編米国法典第119条(a)項に基いて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)

(Filing Date)

(Application No.)

(Filing Date)

(出願番号)

(出願日)

(出願番号)

(出願日)

私は、下記の米国法典第35編120条に基いて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日まで期間中に入手された、連邦規則法典第37編1.56項で定義された特許実務の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.)

(Filing Date)

(Status: Patented, Pending, Abandoned)

(出願番号)

(出願日)

(状況: 特許許可済、係属中、放棄済)

(Application No.)

(Filing Date)

(Status: Patented, Pending, Abandoned)

(出願番号)

(出願日)

(状況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編1001条に基き、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣言を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration  
(日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (*list name and registration number*).

Ronald P. Kananen	24,104
John E. McGarry	22,360
H. Lawrence Smith	24,900
Ralph T. Rader	28,772
Joseph V. Coppola, Sr.	33,373
Michael B. Stewart	36,018
Shmuel Livnat	33,949
Steven L. Nichols	40,326
Glenn E. Forbis	40,610
Kevin D. Rutherford	40,412
Alexander D. Rabinovich	37,425
Matthew J. Russo	41,282
Monica Millner	42,894

David L. Benson	42,314
Joel E. Bair	33,356
Richard D. Gruer	22,388
Michael D. Fishman	31,951
Mark A. Davis	37,118
Stefan V. Chemielewski	39,914
Annette R. Carrothers	40,548
Kristin L. Murphy	41,212
Christopher M. Tanner	41,518
Paul D. Amrozowicz	45,264
G. Thomas Williams	42,228
John W. Rass	38,276

## 書類送付先

Monica Millner  
Rader, Fishman & Grauer PLLC  
1233 20<sup>th</sup> Street, N.W. Suite 501  
Washington, D.C. 20036

## Send Correspondence to:

Monica Millner  
Rader, Fishman & Grauer PLLC  
1233 20<sup>th</sup> Street, N.W. Suite 501  
Washington, D.C. 20036

## 直接電話連絡先: (名前及び電話番号)

Telephone: (202) 955-3750  
Facsimile: (202) 955-3751

## Direct Telephone Calls to: (name and telephone number)

Telephone: (202) 955-3750  
Facsimile: (202) 955-3751

唯一または第一発明者名	Full name of sole or first inventor	Kiyoshi WASHINO
発明者の署名	Inventor's signature	Kiyoshi Washino
住所	Residence	Kanagawa, Japan
国籍	Citizenship	Japan
私書箱	Post Office Address	411-101, Shibonuchi, Takatsu-ku, Kawasaki-shi, Kanagawa 213-0023, Japan
第二共同発明者	Full name of second joint inventor, if any	Akihiro TOCHI
第二共同発明者の署名	Second inventor's signature	Akihiro Tochi
住所	Residence	Kanagawa, Japan
国籍	Citizenship	Japan
私書箱	Post Office Address	2-3-27, Edahigashi, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-0005, Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)